

LAND USE

175 Attachment 5

City of Margate
Appendix C
Streetscape Standards Construction Details

<p>TYPICAL SIDEWALK PAVING PATTERN DETAIL N.T.S.</p> <p>BRICK PAVES PATTERN TO MATCH NORTH SIDE OF NEAREST DRIVE BETWEEN DRIVEWAY DRIVE AND DRIVEWAY DRIVE.</p> <p>1" MIN. CONC. CURB TO BE SAWCUT FOR INSTALLATION OF CURBING SURFACE. FLAGGED IN SIDEWALK (ELECTRICAL, FIRE SIGNAL, WATER METER, ETC.).</p>	<p>BRICK PAVER SIDEWALK/CONCRETE SIDEWALK DETAIL N.T.S.</p> <p>1. PAVERS SHALL BE 4" x 8" x 2-1/2" "TRADITIONAL" AS MANUFACTURED BY E.P. HENRY OR APPROVED EQUAL. SEE CONSTRUCTION PLANS FOR PAVES LOCATION.</p> <p>2. PAVES COLORS SHALL BE RED.</p>	<p>LIGHT DETAIL N.T.S.</p> <p>1. PLANT SUPPORT TO BE ASSEMBLED ON SITE.</p> <p>2. POLE FOR PLANT SUPPORT AREA TO BE DRILLED BY MANUFACTURER.</p> <p>3. SURFACE AREA ORIENTATION TO BE PARALLEL WITH CURB.</p>	<p>TREE PIT SECTION N.T.S.</p> <p>1. TREE SHALL BE 2-1/2" DIA. (MIN.) AT GRADE.</p> <p>2. TREE SHALL BE 2-1/2" DIA. (MIN.) AT GRADE.</p>
<p>TREE PLANTING PIT DETAIL N.T.S.</p> <p>4" x 8" x 2-1/2" PRECAST PAVES FOR CURB SIDE.</p>	<p>TREE GRATE DETAIL N.T.S.</p> <p>NOTE: HENRY FURNACE COMPANY 8-1074-A TREE GRATE WEIGHT 50# 8-1000 TYPE F FRAME WITH BLACK POWDER COATED FINISH. 1/2" MIN. MINIMUM THICKNESS OF APPROVED EQUAL.</p>	<p>SANITARY SEWER CLEANOUT ACCESS FRAME AND COVER DETAIL N.T.S.</p> <p>1. CLEANOUT COVER TO BE 12" DIA. ACCESS COVER.</p> <p>2. CLEANOUT COVER TO BE 12" DIA. ACCESS COVER.</p>	<p>STREET SIGNS INSTALLATION DETAIL N.T.S.</p> <p>1. 3/4" ALUMINUM SIGN BRACKET 6" x 30" L (COPY BOTH SIDES).</p> <p>2. 1/2" x 1/2" x 1/2" (COPY BOTH SIDES) (8000 METRO WIND BRACKET OR EQUAL).</p>
<p>TREE GRATE FRAME MOUNTING DETAIL N.T.S.</p> <p>1. 1/2" DIA. ACCESS COVER.</p>	<p>ORNAMENTAL TRENCH GRATE DETAIL N.T.S.</p> <p>1. 1/2" DIA. ACCESS COVER.</p>	<p>STREET SIGN POLE DETAIL N.T.S.</p> <p>1. 2" O.D. SMOOTH 40 BUSHING ALUMINUM PIPE FINISH TO MATCH LIGHT POLES.</p>	<p>STREET SIGN POLE DETAIL N.T.S.</p> <p>1. 2" O.D. SMOOTH 40 BUSHING ALUMINUM PIPE FINISH TO MATCH LIGHT POLES.</p>